

Hose to ventilation

GeoFlex Weld

GeoFlex Weld for extraction of welding fumes, vapors, ventilation of tanks etc. The hose is very suitable for use together with our extraction arms or portable fan PM-180-1.

Material

PVC coated polyester fabric

Colour

Black

Length

2, 3, 4, 5 or 10 m.

Special length after request

Temperature resistance

- 10 °C til + 60 °C (short 110 °C.)

Application

Air-conditioning,

Extraction of air and welding fumes

Properties

Light weight

Very flexible

Flame retardant according to NF P 92-503 M2



GeoFlex Weld

Technical specifications

Art. No	Diam. (mm)	Weight (kg/m)	Bend. Rad. (mm)	Max. over-pressure (kPa)	Max. Vacuum (kPa)
09-301	40	0,10	23	25,0	15,0
09-302	50	0,12	29	24,0	14,5
09-303	63	0,15	36	18,5	10,5
09-306*	80	0,19	43	15,0	7,0
09-307*	102	0,24	54	12,0	5,0
09-310*	127	0,32	67	10,0	3,5
09-312	152	0,37	79	8,0	3,5
09-313*	165	0,46	86	7,5	2,5
09-314*	200	0,60	105	6,0	2,0
09-315	250	0,77	129	5,0	1,0
09-316A*	315	0,96	162	4,0	0,5
09-317	350	1,09	179	3,5	0,5
09-318	400	1,26	204	3,0	0,5
09-320	500	1,54	256	2,0	0,5

*= Stock items